



(B2)

- THIS DRAWING IS MEANT TO PROVIDE CUSTOMER MOUNTING DATA ONLY. ALL DIMENSIONS ARE REFERENCE UNLESS OTHERWISE NOTED.
- THE TORQUE INFORMATION CONTAINED IN THIS DOCUMENT IS FOR REFERENCE ONLY. IT IS RECOMMENDED THAT THIS BRAKE BE TESTED IN THE SPECIFIC APPLICATION TO VERIFY PERFORMANCE.
- MAXIMUM OPERATING PRESSURE IS 3000 PSI. PRESSURE SPIKES AND SURGES NOT TO EXCEED 4000 PSI.

BPD	B6	22093	WAS Ø0.560	06-23-05	TEH
BPD	B5	22093	ADDED Ø7.80	06-23-05	TEH
BPD	B4	22093	ADDED 2.254 2 PLCS	06-23-05	TEH
BPD	B3	22093	REMOVED Ø7.94	06-23-05	TEH
BPD	B2	22093	ADDED NOTES 1 & 2	06-23-05	LTC
BPD	B1	22093	REDRAWN PRO/E	06-23-05	LTC
TEH	A	10750	RELEASE FOR PRODUCTION	02-02-98	SJS
CHKR	SYM	ECO	DESCRIPTION	DATE	BY

DO NOT SCALE THIS DRAWING
 PROPRIETARY DATA: NOT TO BE
 DISCLOSED, USED, OR DUPLICATED
 FOR PROCUREMENT OR MANUFACTURING
 PURPOSES, EXCEPT AS AUTHORIZED
 IN WRITING BY AUSCO, INC.



C	C	5400	150	14T 12/24	14T 12/24	PROJECT	DATE	PART NAME
MOTOR	REDUCER	RATED TORQUE (LB IN)	RELEASE PRESSURE (PSI)	INPUT (INTERNAL)	OUTPUT (EXTERNAL)	4579	06-25-97	BRAKE MULTI-DISC "C" DRY
MOUNTING FLANGE SAE J744				SPLINE DATA		DESIGNER	SCALE	PART NUMBER
						B. DENNIS	1.000	CC75632