



(B2)

1. THIS DRAWING IS MEANT TO PROVIDE CUSTOMER MOUNTING DATA ONLY. ALL DIMENSIONS ARE REFERENCE UNLESS OTHERWISE NOTED.
2. THE TORQUE INFORMATION CONTAINED IN THIS DOCUMENT IS FOR REFERENCE ONLY. IT IS RECOMMENDED THAT THIS BRAKE BE TESTED IN THE SPECIFIC APPLICATION TO VERIFY PERFORMANCE.
3. MAXIMUM OPERATING PRESSURE IS 3000 PSI. PRESSURE SPIKES AND SURGES NOT TO EXCEED 4000 PSI.

| | | | | | |
|------|-----|-------|------------------------|----------|-----|
| BPD | B8 | 22096 | REMOVED CHAMFER DIM. | 01-25-05 | TEH |
| BPD | B7 | 22096 | WAS PROJECT 4323 | 01-25-05 | TEH |
| BPD | B6 | 22096 | WAS Ø 0.560 | 01-25-05 | TEH |
| BPD | B5 | 22096 | ADDED 2.254 2 PLCS | 01-25-05 | TEH |
| BPD | B4 | 22096 | ADDED Ø 7.80 | 01-25-05 | TEH |
| BPD | B3 | 22096 | REMOVED Ø 7.94 | 01-25-05 | TEH |
| BPD | B2 | 22096 | ADDED NOTES 1 & 2 | 06-24-05 | LTC |
| BPD | B1 | 22096 | REDRAWN IN PRO/E | 06-24-04 | LTC |
| TEH | A | 10751 | RELEASE FOR PRODUCTION | 02-04-98 | SJS |
| CHKR | SYM | ECO | DESCRIPTION | DATE | BY |

DO NOT SCALE THIS DRAWING
 PROPRIETARY DATA: NOT TO BE
 DISCLOSED, USED, OR REPLICATED
 FOR PROCUREMENT OR MANUFACTURING
 PURPOSES, EXCEPT AS AUTHORIZED
 IN WRITING BY AUSCO, INC.



| | | | | | | | | |
|--------------------------|---------|----------------------|------------------------|------------------|-------------------|-----------|----------|--------------------------|
| C | C | 9000 | 230 | 14T 12/24 | 14T 12/24 | PROJECT | DATE | PART NAME |
| MOTOR | REDUCER | RATED TORQUE (LB IN) | RELEASE PRESSURE (PSI) | INPUT (INTERNAL) | OUTPUT (EXTERNAL) | 4579 | 06-25-97 | BRAKE MULTI-DISC "C" DRY |
| MOUNTING FLANGE SAE J744 | | | | SPLINE DATA | | DESIGNER | SCALE | PART NUMBER |
| | | | | | | B. DENNIS | 1.000 | CC75633 |