



- NOTES:
1. THIS DRAWING IS MEANT TO PROVIDE CUSTOMER MOUNTING DATA ONLY. ALL DIMENSIONS ARE REFERENCE UNLESS OTHERWISE NOTED.
 2. THE TORQUE INFORMATION CONTAINED IN THIS DOCUMENT IS FOR REFERENCE ONLY. IT IS RECOMMENDED THAT THIS BRAKE BE TESTED IN THE SPECIFIC APPLICATION TO VERIFY PERFORMANCE.
 3. MAXIMUM OPERATING PRESSURE IS 3000 PSI [207 BAR]. PRESSURE SPIKES AND SURGES NOT TO EXCEED 4000 PSI [275 BAR].

B	B	3200 [362]	190 [13]	15T 16/32	13T 16/32
MOTOR	REDUCER	RATED TORQUE (LB IN) [Nm]	RELEASE PRESSURE (PSI) [BAR]	INPUT (INTERNAL)	OUTPUT (EXTERNAL)
MOUNTING FLANGE SAE J744		SPLINE DATA			

NDC	B	30682	UPDATED PICTORIALY	02-26-20	DJS
NDC	A	30682	RELEASE FOR PRODUCTION	02-20-20	DJS
CHKR	SYM	ECO	DESCRIPTION	DATE	BY
DO NOT SCALE THIS DRAWING. PROPRIETARY DATA: NOT TO BE DISCLOSED, USED, OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES, EXCEPT AS AUTHORIZED IN WRITING BY AUSCO, INC.					
PROJECT	DATE	PART NAME CUSTOMER CONFIGURATION			
ADR30682	02-20-20	M/D DRY "B" BRAKE			
DESIGNER	SCALE	PART NUMBER			
DJ SCHMIDT	1.000	CC105265			